

TECHNICAL BULLETIN A/C LEVELING COMPOUND WCP #653

PAVEMENT MAINTENANCE SYSTEMS

ASPHALT SEALCOATS

1.0 DESCRIPTION AND RECOMMENDED USE

A/C LEVELING COMPOUND (WCP #653) is a blend of an asphaltic emulsion, mineral fillers, glass fiber, ground rubber and plasticizers. It is designed to remain pliable especially in alligatoring skin patch areas. It is also used for filling cracks in excess of 1/2" width in any asphaltic surfaces.

Economically, A/C LEVELING COMPOUND has superior advantages over hot mix and skin asphalt as far as labor and equipment needed to dig out the alligatoring areas and replace it. It is ready to use on asphaltic surfaces such as alligatoring areas, athletic courts, driveways, playgrounds, walkways and running tracks.

2.0 SURFACE PREPERATION

Surface must be dry, clean and free from all loose material, dirt and dust.

3.0 APPLICATION

Mix well before using. Do not dilute. When filling cracks, scrape off excess from surface using a V-shape rubber squeegee before material sets up. A/C LEVELING COMPOUND will set under good conditions, in several hours, depending on weather and filler thickness. Do not use when rain is in the forecast, on wet surfaces or when asphalt and air temperature is below 55 degrees Fahrenheit.

4.0 COVERAGE

Up to 20 sq.ft. for patching alligatoring areas. Up to 75 linear feet per gallon of 1/2" x 1/2" depth cracks.

5.0 CLEAN UP

Use clean water before product has dried. Wash tools in water. Dried product may be removed using WCP #2000.

6.0 PRECAUTIONS

Do not store in direct sunlight or where temperatures exceed 100 degrees Fahrenheit. Container should be closed when not in use. Keep out of reach of children. Do not use when rain is forecast, on wet surfaces or when asphalt and air temperature is below 55 degrees Fahrenheit. Refer to MSDS (available upon request).

7.0 SHELF-LIFE

Up to six months in unopened container.

8.0 AVAILABILITY

5 Gallon Pails

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with Western Colloid instructions. Western Colloid does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at Western Colloid's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Western Colloid in writing at the addresses shown herein. THIS LIMITED WARRENTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRENTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES OR LIMITATIONS ON HOW LONG AN IMPLIED WARRENTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRENTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE.

653_0104