

TECHNICAL BULLETIN

WCP #651

"FLEX CRACK" Cold Pour Crack Filler

PAVEMENT MAINTENANCE SYSTEMS

ASPHALT SEALCOATS

DESCRIPTION AND RECOMMENDED USE 1.0

FLEX-CRACK COLD POUR (WCP #651) is a rubberized asphalt emulsion with greater flexibility designed for filling narrow pavement cracks up to 1/2" in width, in asphaltic, as well as, concrete surfaces. Product designed with resilient characteristics that can allow a threading quality or memory, excellent flow properties and no pin holing. Ready to use on parking lots, airports, athletic courts, driveways, traffic safety islands, playgrounds and walkways.

1.1 **MATERIAL SPECIFICATIONS**

FLEX-CRACK COLD POUR (WCP #651) meets emulsified asphalts - AASHTO Designation M 140-70 - ASTM D 977-73 and D-244 Testing Emulsified Asphalts.

2.0 SURFACE PREPARATION

Surface must be dry, clean, and free from all loose material, dirt and dust. Fill cracks exceeding 1/2" (width up to 1") with A/C Leveling Compound (WCP #653). Oil contaminated cracks can be treated with Western Colloid POLY OIL SEAL (WCP #601).

APPLICATION 3.0

Mix well before using. Use as is. Pour FLEX-CRACK into cracks completely. Before FLEX-CRACK sets up, scrape excess from surface using a rubber squeegee; allow to cure completely before sealing with a mechanical applicator. FLEX-CRACK will set under good conditions in several hours, depending on weather and filler thickness.

4.0 COVERAGE

For estimation purposes - up to 150 linear feet of 1/2" x 1/4" depth crack per gallon.

5.0 **CLEAN UP**

Use clean water before product has dried. Wash tools in water. Dried product may be removed using WCP #2000.

6.0 PRECAUTIONS

Do not store in direct sunlight or where temperatures exceed 100 degrees Fahrenheit. Container should be closed when not in use. Keep out of reach of children. Do not use when rain is forecast, on wet surfaces or when asphalt and air temperature is below 55 degrees Fahrenheit. Refer to MSDS (available upon request).

7.0 SHELF-LIFE

Up to six months in unopened container.

8.0 **AVAILABILITY**

5 Gallon Pails

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with Western Colloid instructions. Western Colloid does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at Western Colloid's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given to Western Colloid in writing at the addresses shown herein. THIS LIMITED WARRENTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRENTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES OR LIMITATIONS ON HOW LONG AN IMPLIED WARRENTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU. THIS WARRENTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS THAT VARY FROM STATE TO STATE.